

Ozone Compatible Air Vent

Ozone Air Vent, Ozone Degasser

This ozone compatible air vent safely removes ozone from pressurized vessels. All ozone compatible materials ensure years of life. See-through material allows quick visual inspection.



Features

- safely removes ozone
- completely ozone compatible
- quick installation
- see-through body shows it is working
- rugged and dependable

Product ID: **AVO3**
In Stock: **Yes**
Price: **\$199**

Specifications

Operating Pressure	150 PSI (10 bar)
Process connection	3/4" FPT (on bottom)
Outlet connection	1/2" FPT
wetted parts	304 & 316L SS, Polysulfone, Viton, Polybutylene Terephthalate (PBT)
Maximum Operating Temp	150-deg F (65.5-deg C)
Maximum gas removal	4.3 SCFM @ 15-PSI pressure differential, 24.3 SCFM @ 150-PSI pressure differential
Dimensions	6.75-in High x 3.5-in diameter (17.2 cm x 9.0 cm)
Weight	1-lb (0.5 kg)

Air Vent on a U-tube



This air vent removes undissolved ozone gas for eventual reinjection into a separate water line at a Talapia fish farm.

Air Vent on Waterzone



The AVO3 can be used traditionally as an air vent or as a water trap. The Waterzone system uses 2 AVO3 vents, one is used as a water trap to drain any water that leaks past the check valves before it damages the ozone generator.