

PVC Ozone Destruct Unit

30-SCFH Ozone Destruct Unit

Inexpensive ozone destruct unit for removing high concentrations of ozone efficiently.



Features

- 30-SCFH flowrate at max 1% ozone
- very efficient
- constructed of high impact PVC
- True catalytic reaction, no consumables
- O₂ & heat are the only by-products
- quick & easy hook-up

Product ID: **ODS-2P**
In Stock: **Yes**
Price: **\$80**

Specifications

Process Flowrate	30-SCFH (14 lpm)
Efficiency	99.96%
Connections	1/4- in Kynar barb connection (orders of 3 or more can choose their connection)
Max ozone concentration	1% dry ozone gas (14.3 g/m ³)
Materials of Construction	PVC, Stainless Steel & Kynar
Rechargeable	No
Pressure Drop	maximum of 0.25 psig at rated flow (30-SCFH) (14 lpm)
Dimensions	2.75-in diameter x 10.5-in long (7-cm x 27-cm)
Weight	2-lbs (1 kg)

ODS-P Product Line



Size range of ODS-P Ozone Destruct Units. The ODS-2P is in the middle. The ODS-3 (left) is the largest PVC Ozone Destruct unit we currently make. Larger units are available upon request.

ODS Product Line



Size range of our non-heated ozone destruct units.