

3 SCFM Ozone Destruct Unit

Ozone Destruct unit for dry process air applications

The ODS-3P is a low priced PVC Ozone Destruct unit that can destroy low concentration ozone in gas streams (less than 1% conc. by wt.) up to 3 SCFM. The PVC design allows for low cost assembly with many of the benefits of the more expensive models



Features

- 3-SCFM flowrate at 1% ozone
- Very efficient ozone destruction
- Constructed of high impact PVC
- low pressure drop
- True catalytic reaction, no consumables
- O₂ & heat are the only by-products

Product ID: **ODS-3P**
 In Stock: **Yes**
 Price: **\$190**

Specifications

Process Flowrate:	3 SCFM
Efficiency:	99.9%
Connections:	3/8-inch Female NPT
Ozone Concentration:	3% Maximum at 0.5 CFM, 1% Maximum at 3 CFM
Catalyst:	Replaceable Catalyst through removable fittings
Pressure Drop:	maximum of 0.5 psig at rated flow (3-SCFM)
Dimensions:	4-inch length x 12-inch height
Weight:	10 Lbs (4.5 kg)

ODS-P Product Line



Size range of ODS-P Ozone Destruct Units. The ODS-3 is the largest PVC Ozone Destruct unit we make.

ODS Product Line



Size range of our non-heated ozone destruct units.